



## FEATURES:

- » Quiet, durable and dependable CS-18GA.K 2-conductor, unshielded audio cable
- » Terminated with high quality nickel-plated 1/4" connectors for years of superior performance and maximum value
- » Individually tested to meet performance and quality requirements
- » 1-year limited warranty

## DESCRIPTION:

StageMASTER Speaker Cables are designed to be quiet, durable and dependable. They are hand-soldered to perfection using top quality metal 1/4" connectors and extremely low-noise cable.

Available with straight 1/4" phone plugs on each end, in 3, 6, 10, 15, 20, 25 and 50 foot lengths.

Our StageMASTER cables are not "outsourced." They are manufactured in our facilities, by our employees, according to the strictest quality standards that we have developed in our more than 25 years in business.

You can depend on StageMASTER SRS Speaker Cables to perform night after night.

## WIRE SPECIFICATIONS:

WIRE:	CS-18GA.K 16 AWG, 2-Conductor	
NUMBER OF CONDUCTORS:	2	
CONDUCTOR GAUGE:	18 AWG	0.823 mm <sup>2</sup>
STRANDING <i>no. strands x AWG</i> :	16 x 30	16 x .051 mm <sup>2</sup>
CONDUCTOR MATERIAL	Bare Annealed Copper	
INSULATION:	.012"	.305 mm
INSULATION MATERIAL:	Polyvinyl Chloride	
INSULATION DIAMETER:	.070"	1.78 mm
LAY LENGTH:	1.5" ±0.05" Left Hand	
FILLER MATERIAL:	Jute	
SEPARATOR:	.001" Paper Tape Applied Longitudinally	
JACKET MATERIAL:	Matte Polyvinyl Chloride	
JACKET COLOR:	Black	
JACKET WALL THICKNESS:	.035"	.889 mm
OUTER DIAMETER:	.215" ± .010	5.46 ± .254 mm