

Description: 2 conductor 22 AWG stranded bare copper, polypropylene insulated, shielded, PVC jacketed installation microphone cable

VTG Part Number: MIC2.

1. Conductor
 - 1.1 AWG Size and Stranding: 22 AWG 7 strands 30 AWG
 - 1.2 Material: Bare annealed copper
2. Insulation
 - 2.1 Material: Polypropylene
 - 2.2 Wall Thickness: .008" nominal
 - 2.3 Diameter: .046" nominal
3. Color Code
 - 3.1 Code: Black and red
4. Assembly
 - 4.1 Assembly: Conductors cabled left hand lay
 - 4.2 Drain Wire: 24 AWG 7/32 tinned copper
 - 4.3 Shield: .001" aluminum/polyester tape
5. Jacket
 - 5.1 Material: Polyvinyl chloride
 - 5.2 Colors: Black, gray, green, pink, brown, orange, purple, red, white and yellow
 - 5.3 Wall Thickness: .023" nominal
 - 5.4 Diameter: .140"
6. Markings
 - 6.1 Type: Surface printing in white ink on black jacket, black in on all colors.
Black print has sequential footage marks
 - 6.2 Legend: VTG AUDIO 22 AWG TYPE CL3 (UL) E156866 – MADE IN U.S.A. XXXXX FEET
7. Electrical Specifications
 - 7.1 Capacitance Between Conductors: 32 pF/ft @ 1 kHz
 - 7.2 Capacitance Conductor to Shield: 58 pF/ft @ 1 kHz
 - 7.3 Characteristic Impedance: 45 ohms @ 1 MHz
 - 7.4 Resistance at 20C: 15.3 ohms/1000 ft.

Dr. No.: 0712A-2
By: TRM
Date: 05/10/04
Page 1 of 1