

Model	# of Cond	Cond gauge & Stranding	Shield Type & Coverage	Overall Diamter (inches)	Nominal Cap. (pF/ft @ 1 kHz)	Char. Imp @ 1Mhz	Available Colors	Weight per 1000 ft (lbs)
MIC1.*	2	24, 16 x 36	Spiral, 95%	0.230	21	70	K, B, G, P, R, W, NB, NG, NO, NP, NY, TB, TG, TK, TM, TO, TP, TR, TY	31
MIC2.*	2	24, 7 x 30	Alum/Poly Tape, 100%	0.140	32	45	K, B, E, G, N, O, P, R, W, Y	15
MIC3.K	2	24, 105 x 44	Braid, 80%	0.175	32	45	K	23
MIC4.*	4	24, 40 x 40	Braid, 95%	0.235	46	44	K, B, E, G, N, O, P, R, W, Y	40
MIC5.*	2	20, 41 x 36	Braid, 85%	0.260	21	70	K, B, R	50
MIDI.*	4	24, 19 x 36	Spiral, 95%	0.230	46	44	K, B, G, O, P, R, W, Y	98
8412.*	2	20, 26 x 34	Braid, 85%	0.262	30	52	K, B, R, Y	47
ROADHOG-J-CLOTH	2	24, 16 x 36	Spiral, 95%	0.295	21	70	K	?
ROADHOG-PRO-M.K	2	20, 41 x 36	Braid, 85%	0.295	21	70	K	?
ROADHOG-RSMCA.K	2	24, 16 x 36	Spiral, 95%	0.295	21	70	K	?
SFMIC4.C	4	24, 19 x 36	Braid, 95%	0.265	46	44	C	?
SFMIC5.C	2	22, 19 x 34	Braid, 85%	0.260	17	90	C	?

MICROPHONE WIRE