

Description: 2 conductors 24 AWG stranded bare copper, polypropylene insulated,
overall serve shielded, PVC jacketed microphone cable

VTG Part Number: ROADHOG-J.K

1. Conductor
 - 1.1 AWG Size and Stranding: 24 AWG 16 strands 36 AWG
 - 1.2 Material: Bare annealed copper
2. Insulation
 - 2.1 Material: Polypropylene
 - 2.2 Wall Thickness: .013" nominal
 - 2.3 Diameter: .050" +/- .002"
3. Color Code
 - 3.1 Code: Blue paired with red
4. Assembly
 - 4.1 Lay Length: 1 3/4" maximum left hand
 - 4.2 Fillers: Jute as required
5. Shield
 - 5.1 Material: Bare annealed copper serve
 - 5.2 Coverage: 95% nominal
6. Jacket
 - 6.1 Material: Matte finish polyvinyl chloride
 - 6.2 Color: Black
 - 6.3 Wall Thickness: .090" nominal
 - 6.4 Diameter: .295 +/- .005"
7. Markings
 - 7.1 Type: Surface printing in white ink
 - 7.2 Legend: ROADHOG BY VTG AUDIO ~ RSMCA-TWIN 24 GA
CONDUCTORS W/HD-SERV SHIELD ASSURING MAXIMUM
AUDIO TRANSPARENCY AND SONIC CLARITY MADE IN U.S.A.
8. Electrical Specifications
 - 8.1 Capacitance Between Conductors: 21 pF/ft @ 1 kHz
 - 8.2 Capacitance Conductor to Shield: 37 pF/ft @ 1 kHz
 - 8.3 Characteristic Impedance: 70 ohms @ 1 MHz
 - 8.4 Resistance at 20C: 23 ohms/1000 ft.

Dr. No.: 0140K-4
By: TRM
Date: 05/19/04
Page 1 of 1