

Description: Multi-conductor 13 AWG stranded bare copper, PVC insulated, unshielded, PVC jacketed speaker cable

1. Conductor

1.1 AWG Size and Stranding: 13 AWG 52 strands 30 AWG

1.2 Material: Bare annealed copper

2. Insulation

2.1 Material: Polyvinyl chloride

2.2 Wall Thickness: .020" nominal

2.3 Diameter: .127" nominal

3. Color Code

3.1 Code: 1. Yellow

2. White

3. Black

4. Orange

5. Blue

6. Brown

7. Green

8. Red

4. Assembly

4.1 Lay Length: Per chart

4.2 Fillers: Jute as required

4.2 Separator: .001" paper tape



5. Jacket

5.1 Material: Polyvinyl chloride, matte finish

5.2 Wall Thickness: Per chart

5.3 Diameter: Per chart

5.4 Color: Black

6. Markings

6.1 Type: Surface printing in white ink

6.2 Legend: VTG AUDIO PROFESSIONAL SERIES COMMERCIAL GRADE
X CONDUCTOR SPEAKER CABLE – MADE IN U.S.A.

VTG P/N	No. of Conductors	Lay Length	Jacket Thick.	Overall Diameter
SPEAKER4	4	5"	.055"	.420" +/- .010"
SPEAKER6	6	6"	.055"	.500" +/- .010"
SPEAKER8	8	7"	.060"	.545" +/- .010"



Dr. No.: 0111B-5

By: TRM

Date: 05/10/04

Page 1 of 1